

# RG59 E80+VDE COAXIAL CABLE

### **APPLICATION**

❖ High quality RG Type Coaxial cable,75 Ohm suitable for many applications, particularly broadcast and CCTV installations.


### **PRODUCT FACTS**

- ❖ INDOOR USE, Accepts 100m longer (signal cable with DC power)
- Suitable for shop-lot, home
- ❖ 2core power 30x0.15mm LC

## **PRODUCT CODE**

- \* RG59-ALL-E80VDE-100M
- ❖ RG59-ALL-E80VDE-250M

## **TECHNICAL DATA**



ITEM		UNIT	SPEC. VALUE
Inner Conductor	Material		Copper clad steel
	Dia.(approx)	mm	$0.81 \pm 0.15$
Insulation	Material		Foam Polyethylene
	Nom. Thickness	mm	$1.56 \pm 0.18$
	Dia.(approx)	mm	$3.70 \pm 0.18$
	Colour		Natural
Outer Conductor	Type		Braid
	Material		Copper clad Aluminum
	Coverage	%	$83 \pm 3$
	Dia.(approx)	mm	0.12 x 64
Jacket	Material		PVC
	Nom. Thickness	mm	$0.80 \pm 0.2$
	Colour		Black
	Dia.(approx)	mm	$5.90 \pm 0.20$
CHARACTERISTICS			
DC Conductor Resistance at 20°C			< 26.1Ω/100m
Insulation Resistance at 20°C			$> 200 \text{ M}\Omega.\text{m}$
Nominal Velocity of Propagation			$66.6 \pm 3\%$
Capacitance			$67 \pm 5 \text{ pF/m}$
Characteristic Impedance at 20°C,200MHz			$75 \pm 5\Omega$
PACKING			WEIGHT
Roll	100m/roll		
Wooden drum	250m/drum		