

Wireless Perimeter Detectors Glass Break Detector



G550 Wireless Glass Break Detector

► Features

- Detects breaking of different types of glass including plated, tempered, laminated and wired
- Wireless range: 6 meter (20 ft) radius range and 360° coverage pattern protects an entire room with one sensor
- Factory-set sensitivity for quick and safe installation

► Specifications

Power	3 x AAA alkaline batteries
RF Frequency	433 or 868 MHz
Battery Life	2 years
Wireless Range	20m (65 ft) with MG6250 40m (130 ft) with MG5000 / MG5050 / RTX3; in a typical residential environment
Operating Temperature	0 to 50 °C (32 to 120 °F)
Dimensions	10.9 x 7.9 x 4.3 cm (4.3 x 3.1 x 1.7 in.)



5709C Acoustic Glass Break Sensor Tester

► Features

- Compatibility with the G550 Wireless Glass Break Detector
- Provides real glass break sounds
- Recommended size of glass: 1 x 2 ft or larger; Minimum 1 x 1 ft
- Recommended for glass thickness as follows:
 - Plate glass: 3/3 to 1/4 in.
 - Tempered glass: 1/8 to 1/4 in.
 - Laminated glass: 1/8 to 1/4 in.

► Specifications

Battery Type	9V
Operating Temperature	0 to 49 °C (32 to 120 °F)
Dimensions	15.9 x 2.8 x 6.4 cm (6.3 x 1.1 x 2.5 in.)

Wireless Perimeter Detectors Door Contact



DCT10 Wireless Long-Range Door Contact

► Features

- 2-zone capabilities where each zone is independent and has its own serial number
 - Zone 1: One of two high-sensitivity reed switches on board (magnet included)
 - Zone 2: Universal input (N.O. / N.C.)
- Low battery and signal transmission LED
- Anti-tamper switch

► Specifications

Input Response Time	45 ms
Power	4.5 Vdc (3 x AAA alkaline batteries)
RF Frequency	433 or 868 MHz
Battery Life	Up to 3 years
Wireless Range	Typical in a residential environment 30m (100 ft) with MG6250 70m (230 ft) with MG5000 / MG5050 / RTX3 / K32LX / K641LX
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	12.4 x 4.5 x 3.3 cm (4.9 x 1.8 x 1.3 in.)



DCT2 Wireless Door Contact

► Features

- One high-sensitivity reed switch (magnet included)
- Anti-tamper switch
- Built-in strip antenna (printed)

► Specifications

Power	1 x 3V lithium battery (DL2450)
RF Frequency	433 or 868 MHz
Battery Life	Between 1 and 5 years
Wireless Range	20m (65 ft) with MG6250 40m (130 ft) with MG5000 / MG5050 / RTX3; in a typical residential environment
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	4.3 x 3 x 1.8 cm (1.7 x 1.2 x 0.7 in.)

