

# REMOTE CONTROLS

## Specifications



	REM1	REM101	REM15	REM25	REM2	REM3
<b>Description</b>	4-Button Remote Control with Backlit Buttons	Emergency / Panic Remote Control	4-Button Remote Control with Backlit Buttons	2-Way Wireless Remote Control with Backlit Buttons	5-Button, 2-Way Remote Control with Backlit Buttons	Hand-Held 2-Way Remote Keypad
<b>RF Frequency</b>	433 or 868 MHz	433 or 868 MHz	433 or 868 MHz	433 or 868 MHz	433 or 868 MHz	433 or 868 MHz
<b>Battery Type</b>	1 x 3V lithium battery (CR2032)	1 x 3V lithium battery (CR2032)	1 x 3V lithium battery (CR2032)	1 x 3V lithium battery (CR2032)	1 x 3V lithium battery (CR2032)	1 x 3V lithium battery (CR2032)
<b>Wireless Range for Typical Residential Environment</b>	30m (100 ft) to 45m (150 ft)	30m (100 ft) to 45m (150 ft)	30m (100 ft) to 45m (150 ft)	30m (100 ft) to 45m (150 ft)	30m (100 ft) to 45m (150 ft)	30m (100 ft) to 45m (150 ft)
<b>Humidity</b>	5 to 90%	5 to 90%	5 to 90%	5 to 90%	5 to 90%	5 to 90%
<b>Operating Temperature</b>	-10 to 55 °C (14 to 131 °F)	-10 to 55 °C (14 to 131 °F)	-10 to 55 °C (14 to 131 °F)	-10 to 55 °C (14 to 131 °F)	-10 to 55 °C (14 to 131 °F)	0 to 50 °C (32 to 120 °F)
<b>Dimensions / Weight</b>	6 x 4.3 x 2 cm (2.3 x 1.7 x 0.8 in.) / 30g (1.05 oz)	5.1 x 3.2 x 1.3 cm (2.0 x 1.2 x 0.5 in.) / 16g (0.5 oz)	6.6 x 3.9 x 1.1 cm (2.6 x 1.5 x 0.4 in.) / 35g (1.2 oz)	3.9 x 7.2 x 1.2 cm (1.5 x 2.8 x 0.5 in.) / 40g (1.4 oz)	7.8 x 3.8 x 1.8 cm (3.1 x 1.5 x 0.7 in.) / 23.4g (0.82 oz)	8 x 3.4 x 1.4 cm (3.1 x 1.3 x 0.6 in.) / 32g (1.2 oz)
<b>Special Features   Certification</b>						

# MOTION DETECTORS - PIR

## Wireless Indoor / Outdoor



	PMD2P	PMD75	NV75MR	PMD85	NV35MR	NV780MR
<b>Page Reference</b>	See page 33	See page 33	See page 34	See page 35	See page 35	See page 34
<b>Indoor / Outdoor</b>	Indoor	Indoor	Indoor	Outdoor	Indoor / Outdoor	Indoor / Outdoor
<b>Sensor</b>	Dual Element	2x Dual Element	2 x Dual Element	2x Dual Element	2x Dual Element	2x Dual Element
<b>Detection Range</b>	11 x 11m (36 x 36 ft);	11 x 11m (36 x 36 ft)	16m (52 ft)	11 x 11m (36 x 36 ft)	Pet: 7.5m x 2m (25 x 7 ft) Sharp: 10 x 2m (33 x 7 ft)	2 x 3m to 12m (9.8 to 39 ft)
<b>Pet Immunity</b>	Pet Tolerance up to 18 kg (40 lb)	Up to 40 kg (90 lb)	Up to 50 cm	Up to 40 kg (90 lb)	50 cm	Up to 40 kg (90 lb)
<b>Digital Detection</b>	-	▲	▲	▲	▲	▲
<b>Auto Temperature Compensation</b>	▲	▲	▲	▲	▲	▲
<b>Dual Edge Processing</b>	-	▲	▲	▲	-	-
<b>Operating Temp.</b>	0 to 50 °C (32 to 122 °F)	0 to 50 °C (32 to 122 °F)	-35 to 50° C (-31 to 122° F)	-35 to 50 °C (-31 to 122 °F)	-35 to 60° C (-31 to 140° F)	-35 to 60 °C (-31 to 140 °F)
<b>Battery Type / Life</b>	3xAAA, 2 years	3xAAA, 2 years	2xAA, 3 years	3xAAA, 3 years	2xAA, 3 years	3xAA, 3 years
<b>Certification</b>						

▲ = included feature