

DHI-LM32-B200

32" FHD Monitor



Features:

- · Light and cost-effective plastic housing
- · suitable for continuous 24/7 operation
- \cdot 178°H/178°V extra-wide viewing angle for overall viewing performance
- \cdot High fidelity digital processing for a brilliant and vivid video
- · 8ms fast response time with no image blurring or ghosting
- · Support multiple signal inputs such as HDMI and VGA
- · Low energy consumption, long service life









Technical Specification		
Model		
Model	DHI-LM32-B2000	
Display		
Screen Size	31.5"	
Aspect Ratio	16:9	
Resolution	1920×1080 (FHD)	
Backlight	LED	
Brightness/Luminance	250 cd/ m³	
Contrast	1400:1	
Display Color	16.7M(8bit)	
Viewing Angle(H/V)	178°(H)/178°(V)	
Response time	8ms	
Refresh Rate	60Hz	
Signals		
Input	VGA×1, HDMI×1,	
General		
Power Supply	AC100~240V (+/-10%), 50/60 Hz	

Consumption (Standard)	40W		
Consumption (Standby)	≤0.5W		
Net Weight	5.1Kg		
Gross Weight	7.5Kg		
Wall Mount	100×100mm		
Dimension without standard (W×H×D)	714.97*189.2*507.41mm		
Package(W×H×D)	784*142*497mm		
W 15 : .	Temperature	0℃~40℃ (32°F~104°F)	
Work Environment	Humidity	10%~85%	
Accessory			
Standard	HDMI cable, power cable, pedestal		
Optional	Hanging bracket		
Certifications			
Certifications	CE/FCC		

Commercial Series | DHI-LM32-B200

Dimensions(mm)

