

# MinuteBank

## VRLA AGM Battery

BT-12M26AT(W)[12V26Ah]



### General Features

- Designed floating charging service life: 8 years (25°C)
- Sealed and maintenance free operation
- Safety valve installation for explosion proof
- Low self-discharge characteristic
- Wide operating temperature range from 0°C~40°C
- Lead Aluminum calcium Tin alloy high energy, prevent corrosion


### Application

- DC power supply
- UPS/EPS power supply
- Electrical devices & instruments
- Security and fire alarm systems
- Telecom stations and power stations
- Medical equipments
- Emergency lighting systems

### Physical Specifications

Nominal Voltage	Nominal Capacity (20HR)	Dimension				Weight ±3%	Internal Resistance (In full charge status)	Standard Terminals
		L	W	H	TH			
12V	26AH	175±2mm	166±2mm	125±2mm	125±2mm	Approx 7.60kg (16. 72lbs)	≈11.2 mΩ	T04 (standard)

### Dimensions



### Battery Discharge Table

End Voltage (V)	Minute (M)						Hour (H)									
	5	10	15	20	30	45	1	1.5	2	3	4	5	6	8	10	20
<b>Constant Current Discharge Data Sheet (Amperes at 25°C)</b>																
10.20	101.0	65.8	51.5	37.3	26.3	19.1	16.4	13.04	9.70	6.82	5.16	4.58	4.14	3.13	2.55	1.35
10.50	95.1	63.2	50.1	36.0	25.5	18.9	16.3	12.80	9.33	6.69	5.05	4.51	4.09	3.11	2.51	1.34
10.80	89.1	60.5	47.6	35.2	24.8	18.5	16.2	12.56	8.96	6.54	4.92	4.42	4.02	3.08	2.45	1.31
<b>Constant Power Discharge Data Sheet (Watt at 25°C)</b>																
10.20	1048	755	612	421.8	345	252	191.6	146.9	110.5	78.89	61.93	52.00	46.97	36.62	29.64	15.96
10.50	974	731	593	417.8	338	246	188.5	144.8	109.0	77.11	60.61	51.41	46.50	36.33	29.19	15.73
10.80	902	695	554	413.7	328	240	185.4	142.6	107.4	75.77	59.09	50.81	45.98	35.95	28.70	15.51

**NOTE :** The battery should be charged within 6 months of storage, Otherwise, permanent loss of capacity might occur as a result of sulfation

## Constant-Voltage Charge

Rated Capacity	
20 hour rate (1.30A)	26.5AH
10 hour rate (2.60A)	25.0AH
5 hour rate (4.42A)	22.0AH
27 minute rate (26A)	13.0AH
7 minute rate (78A)	9.1AH
Capacity affected by Temperature	
40°C(104°F)	103%
25°C(77°F)	100%
0°C(32°F)	86%

Cycle Application
1. Limit initial current less than 6.5A.
2. Charge until battery voltage (under charge) reaches 14.1V to 14.4V at 25°C(77°F).
3. Hold at 14.1V to 14.4V until current drop to under 0.144A for at least 3 hours.
4. Temperature compensation coefficient of charging voltage is -30mV/°C.
Standby Service
1. Hold battery across constant voltage source of 13.6 to 13.8 volts with current limit 6.0A continuously .When held at this voltage , the battery will seek its own current level and maintain itself in a fully charge status.
2. Temperature compensation coefficient of charging voltage is -18mV/°C.

## Performance Characteristics

