

# SCB-6005

2MP Analog Box camera

Analog



FC | UL LISTED | CE | EAC

## Key Features

- Full HD(1920 x 1080, 30fps) resolution
- 0.04Lux@F1.2 (Color), 0.004Lux@F1.2(B/W)
- Day & Night(ICR)
- SSNRIV, Motion detection
- Transmission distance max.500m

Video	
Imaging Device	1/2.8" CMOS
Resolution	1920x1080
Max. Framerate	30fps/25fps(60Hz/50Hz)
Min. Illumination	Color: 0.04Lux (F1.2, 1/30sec) BW: 0.004Lux(F1.2)
Video Out	BNC(AHD 2MP,CVBS)
Video Transmission Distance	500m(5C2V Coaxial Cable)
Lens	
Focus Control	Manual
Lens Type	DC auto iris
Mount Type	C/CS
Operational	
Camera Title	Displayed up to 15 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, DWDR
Digital Noise Reduction	SSNRIV
Defog	Support
Motion Detection	4ea
Privacy Masking	8ea, rectangular zones
Gain Control	Low / Middle / High / Very High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	1 ~ 1/12,000sec
Video Rotation	H-REV / V-REV / HV-REV
Analytics	Motion detection
Serial Interface	RS-485: Samsung-T/E, Pelco-D/P, Panasonic, Bosch, Honeywell, Vicon, AD, GE
Alarm I/O	Output 1ea, External D/N 1ea
Alarm Triggers	Analytics
Alarm Events	Alarm output
Coaxial Protocol	ACP(AHD Coax Protocol) CVBS: Pelco-C(Coaxitron)
Environmental & Electrical	
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH
Input Voltage	AC 24V~ 50/60Hz ,DC 12V
Power Consumption	AC 24V / 0.37A (Max 3.6W) DC 12V / 0.32A (Max 3.5W)
Mechanical	
Color / Material	Black, Ivory / Aluminum, Plastic

**Product Dimensions / Weight**

68.4(W)×59.6(H)×92.7(D)mm(2.69×2.35×3.65"), 186g(0.41 lb)

- The latest product information / specification can be found at [hanwha-security.com](http://hanwha-security.com)
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.