

Wired Motion Detectors

Analog



460


Vertical View PIR Motion Detector

► Features

- Ideal for entry / exit protection and exit access requests
- Dual element PIR sensor
- Anti-tamper switch
- Adjustable lens position (0° or 10°)


► Specifications

Detection Range	Hand-sized objects for card access applications: 2 x 1.5m (7 x 5 ft) Body-sized objects for security applications: 6 x 4.5m (20 x 15 ft)
Input Voltage	(12 Vdc mode) 9 to 16 Vdc (24 Vdc mode) 20 to 27 Vdc
Current Consumption	Typical: 15 mA Maximum: 18 mA
Relay Output	N.C. or N.O.
Operating Temperature	-10 to 50 °C (14 to 122 °F)
Dimensions	11.4 x 9.2 x 3.2 cm (4.5 x 3.6 x 1.3 in.)



Wired Special Detectors

Vibration Detector



950

Safe Protector

► Features

- High-sensitivity piezoelectric element
- 5 sensitivity settings
- 2.5m (8.2 ft) protection range
- Anti-tamper switch

► Specifications

Input Voltage	10 to 16 Vdc
Current Consumption	Minimum: 12 mA Maximum: 16 mA
Diameter of Protected Surface	2.5m (8.2 ft)
Alarm Relay	28V / 150 mA
Operating Temperature	-20 to 50 °C (-4 to 122 °F)
Dimensions	6.4 x 11 x 2.4 cm (2.5 x 4.3 x 0.9 in.)



Accessories

Glass Break Sensor Tester



459

Test Trek

► Features

- Produces a test tone to verify the GlassTrek's high-audio frequency detection capability
- Dimensions: 8.2 x 14.3 x 3.8 cm (3.3 x 5.6 x 1.5 in.)